

SYSTEM AND METHOD FOR CABLING COMPUTING EQUIPMENT

Inventor: Jenwei Hsieh  
10806 Scotland Well Drive  
Austin, Texas 78750

Victor V. Mashayekhi  
2015 Wood Glen Drive  
Round Rock, Texas 78681

Assignee: DELL PRODUCTS L.P.  
One Dell Way  
Round Rock, Texas 78682-2244

BAKER BOTTS L.L.P.  
One Shell Plaza  
910 Louisiana  
Houston, Texas 77002-4995

Attorney's Docket: 016295.0619  
(DC-02474)

ATTORNEY'S DOCKET  
016295.0619  
(DC-02474)

PATENT APPLICATION

1

## SYSTEM AND METHOD FOR CABLING COMPUTING EQUIPMENT

### TECHNICAL FIELD

The present invention relates generally to computer installation instruction and, more particularly, to a system and method for cabling a computing system.

000780" 5E0/EE960

BACKGROUND

Today, computers and their assorted peripherals are generally interconnected with a plurality of cables. In some instances, it may be that only one cable will fit in a particular computer slot and yet, in other cases, it may be possible for multiple cables to fit into a particular computer slot. To solve such problems, many computers and peripherals are being designed to use one communication scheme and therefore one cabling format. Universal Serial Bus is one such technology.

While such measures may become useful in the area of personal computers, large scale computing system implementations, such as server farms and server clusters, do not presently have the same luxury and are such a solution is not being considered. As such, large scale computing system implementations generally require many different cables of many different forms to interconnect many different computing components.

In addition to the task of connecting an appropriate cable to an appropriate port, the computing components used for large scale computing system implementations are often required to be connected in a predetermined topology. The results of cabling such complex computer installations out of order often include unexpected behavior of the system, system lock-ups as well as many additional otherwise avoidable problems. Miscabling in such large scale implementations, not to mention in the area of personal computers, can also result in numerous customer support and service issues.

Currently, the solution to cabling large scale computing systems has generally been to employ a trained cable installer. However, even when employing the services of a trained cable installer, detailed graphs, charts and instructions must still be followed to ensure both proper connections as well as the proper sequencing of connections. With the speed of technological advancement being what it is, whether or not a cable installer has up-to-date cabling instructions may be yet another concern during such an installation.

09637039-081000

SUMMARY

In accordance with teachings of the present disclosure, a system and method are described for cabling a computer system. Accordingly, in one embodiment, a method for cabling a plurality of computing components is provided. The method preferably includes determining a cabling connection to be made between a first computing component and a second computing component. The method preferably further includes generating a signal on the first computing component and the second computing component indicative of the cabling connection to be made.

In an alternate embodiment, an apparatus for cabling a computer system is provided. The apparatus generally includes at least one processor and memory preferably associated with the at least one processor. A management communications interface preferably coupled to a communications network, the processor and the memory is also preferably included in the apparatus. Generally to effect cabling, the apparatus preferably includes a program of instructions storable in the memory and executable in the processor. The program of instructions is preferably operable to generate at least one signal indicative of a cabling connection to be made to at least a first computing component of a plurality of computing components preferably coupled to the communications network.

In yet another embodiment, a computing system preferably including a plurality of computing components is provided. Each of the plurality of computing

components preferably includes a management communications interface preferably coupled to a communications network and at least one port operable to connect to at least one port on at least one of the remaining plurality of computing components. In the computing system, at least one of the plurality of computing components is preferably operable to identify a first computing component to be connected to a second computing component and to identify the second computing component to be connected to the first computing component. Preferably upon identifying the first and second computing components, the at least one computing component may generate at least one signal on the first computing component indicative of a cabling connection to be made between the first computing component and the second computing component.

One technical advantage provided by the present disclosure is a reduction in the number of customer support and service issues resulting from a computer installation.

An additional technical advantage provided by the present disclosure is the ability to adapt cabling instruction to a variety computer installations as well as to available computing components.

Yet another technical advantage provided by the present disclosure is the ability to employ current computing component hardware to effect a complex computing system cable installation.

A more complete understanding of the present embodiments and advantages thereof may be acquired by referring to the following description taken in conjunction with the accompanying drawings, in which like reference numbers indicate like features, and wherein:

FIGURE 2 is a schematic diagram illustrating a computing system to be cabled according to teachings of the present disclosure; and

FIGURE 3 is a flow diagram illustrating a method for cabling a computing system incorporating teachings of the present disclosure.

DETAILED DESCRIPTION

Preferred embodiments and their advantages are best understood by reference to FIGURES 1 through 3, wherein like numbers are used to indicate like and corresponding parts. Accordingly, to overcome limitations and difficulties in current methods of cabling computer installations, a method and system have been developed which are capable of guiding a cable installer through computer installation with multiple components.

FIGURE 1 illustrates one embodiment of a computing system cabled according to teachings of the present disclosure. In addition to the numerous interconnections to be made, computing systems such as computing system 100 must often be cabled in a specific order. As such, FIGURE 1 illustrates one example of the cabling complexity with which computing systems are typically associated. For example, the decision as to whether servers 105a - 105d are to be coupled to switches 110a and 110b before server 105a is coupled to storage unit 115 or whether server 105a is to be coupled to storage unit 115 before coupling switches 110a and 110b to servers 105a - 105d is just one of the many cabling complexities associated with sophisticated computing systems such as computing system 100.

As such, preferably included in computing system 100 are servers 105a - 105d, switches 110a and 110b, storage unit 115 and tape library 120. Computing system 100 may also include one or more routers, hubs, clients as well as various other computing components operable to function as a part of computing system 100.



Servers 105a - 105d preferably include component LEDs 125 (light emitting diode) and device LEDs 130a - 130d. Also preferably included on servers 105a - 105d is management communications interface 135. Similarly, switches 110a and 110b preferably include component LEDs 140, device LEDs 145a - 145j and device LEDs 147a - 147d. Management communications interface 150 is also preferably included on switches 110a and 110b.

Storage unit 115 preferably includes component LED 160, device LEDs 165a - 165d and management communications interface 170. Similarly, tape library 120 preferably includes component LED 175, device LEDs 180a - 180d and management communications interface 185. The uses and purposes of the various component LEDs, device LEDs and management communication interfaces will be described in greater detail below.

Interconnecting the computing components of system 100 are cables or patch cables 190. Depending upon the type of connection to be made between respective computing components, cables 190 may be Ethernet, Gigabit Ethernet, Fibre Channel, USB, Fire Wire, parallel, serial, SCSI or any other format operable to interconnect the computing components of a computing system such as computing system 100.

According to the present disclosure, the cabling of computing system 100 may be enabled by preferably coupling each of the computing components of computing system 100 to management communications network 205 as illustrated in FIGURE 2. Management communications interfaces 135, 150, 170 and 180 preferably enable such

coupling. Management communications network 205 may be a fast Ethernet network, or other network form operable to communicate with one or more computing components on a systems management or higher level. Accordingly,  
5 management communications interfaces 135, 150, 170 and 180 may be Ethernet ports, serial ports, Fibre Channel ports, etc.

Many currently manufactured computing components are generally designed with at least one form of management  
10 communication ability for such purposes as computing component addressing, network configurations, software downloads and the like. Such communication ability enables a cable installer to use laptop computer 210 or another suitable device enabled with teachings of the  
15 present disclosure to communicate with the computing components to be incorporated into a computing system such as computing system 100. By coupling laptop computer 210 enabled with teachings of the present disclosure to management communications network 205,  
20 proper, effective and efficient cabling of computing system 100 may be achieved.

Referring now to FIGURE 3, a flow diagram of a method for cabling a computing system is illustrated. In general, method 300 of FIGURE 3 preferably provides a  
25 cable installer with signals or prompts such that the cable installer may be led through the preferred or proper cabling of a computing system installation. Method 300 may be implemented as a set of instructions that are storable in memory and executable by a processor  
30 of a computing component.

000180-6202560

Upon beginning at step 305, method 300 may effect communication with the plurality of computing components preferably coupled to management communications network 205 such that each of the computing components may be identified, as indicated at step 310. Identification may include obtaining what type of component is to be cabled into a computing system, i.e., server, router, hub, bridge, storage device, etc. Identification of the computing components may also include determining what type of connection will be used for each computing component, i.e., Ethernet connections, SCSI (small computer system interface) connections, Fibre Channel connections, serial connections, etc. Various address assignments associated with each computing component may also be identified during step 310 of method 300. For example, a MAC (Media Access Control) address, IP (Internet protocol) address, Ethernet port address, etc., may be acquired from each computing component to be cabled into a computing system.

Once the computing components to be cabled into a computing system have been identified as desired at step 310, method 300 may proceed to step 315. At step 315, the cabling sequence of the computing components is preferably determined. Such a cabling sequence may be determined one computing component at a time or, an entire computing system cabling sequence may be determined prior to initiation of cabling.

Accordingly, at step 315, a first computing component to be cabled may be identified. Once a first

At step 320, identification of one or more computing components to be cabled to the first computing component identified at step 315 is preferably performed.

Upon identification of the one or more computing components to be cabled to the first computing component, method 300 may proceed to step 325. At step 325, one or more connection points or ports on each computing component to be cabled may be identified. For example, if server 105a has been selected as the first computing component to be cabled and switch 110a is the computing component to which it is to be connected or cabled, it may be preferable to use an Ethernet connection or port on server 105a to cable server 105a to a similar port on switch 110a. Similarly, if server 105a is selected as the first computing component to be cabled and storage unit 115 is the computing component to which server 105a is to be cabled, it may be desirable to use a Fibre

Channel connection or port on server 105a for the cabling connection between the respective computing components. Alternatively, a SCSI connection may be preferred by storage unit 115 thereby requiring a SCSI port on server  
5 105a to be employed for the cabling connection between the respective computing components.

Upon selection of one or more connection points or ports at step 325, method 300 may proceed to step 330. At step 330, guidance for the cabling of the first  
10 computing component to be cabled to the remaining computing components may begin.

At step 330, one or more signals may be generated to indicate to a cable installer the location of the cabling connections to be made. As such, component LEDs 125,  
15 140, 160 and 175 may be employed to first indicate which components are to be cabled together. Subsequently, device LEDs 130a - 130d, 145a - 145j, 147a - 147d, 165a - 165d and 180a - 180d may be employed to indicate which connection points or ports on the identified computing  
20 components are to be cabled. In addition to or in replacement of illuminating LEDs present on the computing components to be cabled, alternate signaling implementations may be employed alone or in combination. Such signaling implementations may include, but are not  
25 limited to, generating beep codes, powering on only selected components, generating flashing codes using assorted LEDs or other indicators, etc. Additionally, different forms of signalling may also be employed to indicate different things. For example, a green LED may  
30 indicate that an Ethernet cable is to be used while a

yellow LED may indicate that a SCSI cable is required. Other embodiments of altering the signal are considered within the scope of the present disclosure.

As an installation example, in a computing system  
5 100 implementation where server 105a is to be coupled to storage unit 110b and switch 110a, method 300 may illuminate component LED 125 of server 105a to indicate that server 105a is the next computing component to be cabled. Next, method 300 may illuminate component LED  
10 140 of switch 110a to indicate that server 105a is to be cabled to switch 110a.

Upon identifying an appropriate port, such as an Ethernet port, on server 105a, method 300 may illuminate device LED 130c to indicate that the device associated  
15 with device LED 130c is to have one end of an appropriate cable connected thereon. In addition, method 300 may also illuminate device LED 145b on switch 110a to indicate that a device associated with device LED 145b is to have the opposite end of the cable connected thereon.  
20 Accordingly, method 300 has indicated to a cable installer that a cable connection is to be made between a device associated with device LED 130c of server 105a and a device associated with device LED 145b of switch 110a.

Upon verifying that no further connections are  
25 desired between server 105a and switch 110a, method 300 may determine that it is now time to cable server 105a to storage unit 115. Accordingly, method 300 may again illuminate component LED 125 of server 105a and component LED 160 of storage unit 115 to indicate that these two  
30 components are to be cabled together. Upon selection of

the appropriate ports or devices to be connected amongst server 105a and storage unit 115, method 300 may illuminate device LED 130a, for example a Fibre Channel port, of server 105a and device LED 165a of storage unit 115 to indicate a cabling connection to be made between  
5 ports on the devices indicated by the respective device LEDs.

In part to effect proper cabling of a computing system 100, it may be desirable to ensure that the  
10 preferred ports or connection points of the current computing components have been cabled as desired. Such a verification is provided for at step 335 of method 300. Accordingly, in one embodiment of method 300, upon generation of the signals indicative of cabling  
15 connections to be made, method 300 may proceed to step 335 of FIGURE 3. At step 335, verification of the cabling connection between the indicated computing components and/or the identified ports or devices may be performed. Such a verification may be employed in such  
20 scenarios where the order in which computing components are to be cabled will have significant effects on computing system 100 performance.

At step 340 of method 300, the computing components currently being connected are evaluated to determine  
25 whether there are additional ports included on the respective computing components which require cabling. If a determination is made that there exists additional ports to be cabled, method 300 may proceed to step 325 for proper identification of the one or more ports to be  
30 cabled and a reiteration of the remaining steps of method

5           At step 345, method 300 may again evaluate the  
computing components connected to management  
communications network 205 to determine whether any  
computing components remain to be cabled. Should one or  
more computing components be identified at step 345 as  
10 requiring cabling connections, method 300 may proceed to  
step 315 such that the next computing components to be  
cabled may be identified, appropriately cabled and a  
reiteration of the remaining steps of method 300. Should  
a determination be made at step 345 that all of the  
15 computing components to be cabled have been cabled,  
method 300 may end at step 350.

In an alternate implementation of method 300, two or more devices may be coupled together using management communications interfaces included thereon. A routine similar to method 300 may be executed on one or more of the devices to indicate the cabling connections to be made between the computing components and the respective port or ports included on each. Through altering the computing components coupled together, an entire computing system may be appropriately and effectively cabled.

AUS01:211407.1



09637033-031000  
installer is able to cable the computing system  
accurately, efficiently and completely without having to  
wrestle with the limitations in existing methods of  
computing system cable installations. The present  
5 disclosure also provides verification that computing  
components of a computer system have been properly cabled  
or interconnected with each other. The present  
disclosure may be applied to generally all types of  
computing components including, but not limited to,  
10 servers, switches, hubs, storage devices, routers, etc.

Although the disclosed embodiments have been  
described in detail, it should be understood that various  
changes, substitutions and alterations can be made to the  
embodiments without departing from their spirit and  
15 scope.